

**BEST AVAILABLE COPY**

Application No. 10/039,892  
Page 2 of 12

**AMENDMENT**In The Claims

1. (currently amended) A high pressure applicator for driving the delivery of a flowable tissue implant material, comprising:

a first column having an inner wall, an outer wall, a first end and a second end having an orifice for delivering implant material therethrough, said first column having a volume greater or equal to the volume of implant material to be delivered, on average, to a vertebral body during a vertebroplasty procedure;

a second column, said second column being drivable with respect to said first column to generate a pressure within said first column; and

a handle attached to said first column and radially extending therefrom to provide a user a mechanical advantage upon grasping said handle

wherein said applicator is capable of generating pressures of at least about 1000 psi.

2. (previously amended) The high pressure applicator of claim 1, further comprising at least one sealing element interfacing with said inner wall of said first column, said at least one sealing element providing for or enhancing generation of said pressure.

3. (Original) The high pressure applicator of claim 1, wherein said second column comprises a wall which is drivably engageable with one of said inner and outer walls.

4. (Original) The high pressure applicator of claim 1, further comprising a handle integrally formed with or affixed to and extending radially from said second column to provide the user a mechanical advantage upon grasping said handle.

5. (withdrawn) The high pressure applicator of claim 1, further comprising threading on said outer wall of said first column, wherein said second column is substantially hollow and comprises an open first end, a closed second end and threading on an inner wall

Application No. 10/039,892

Page 3 of 12

thereof, said threading on said second column being engageable with said threading on said first column.

6. (withdrawn) The high pressure applicator of claim 5, wherein said second column further comprises and extension integrally formed with or affixed to second column and having an end portion extending from said open end of said second column, said extension adapted to be inserted through said open end of said first column and form a substantial pressure seal with said inner wall.

7. (withdrawn) The high pressure applicator of claim 6 further comprising at least one sealing element mounted to said end portion of said extension and adapted to form a pressure seal with said inner wall thereby forming a pressure seal between said first and second columns.

8. (withdrawn) The high pressure applicator of claim 7, wherein said at least one sealing element comprises an O-ring.

9. (withdrawn) The high pressure applicator of claim 5, further comprising a plunger element adapted to be inserted within said first and second columns, said plunger element having a first end portion and a second end portion.

10. (withdrawn) The high pressure applicator of claim 9, wherein said first end portion is adapted and configured to closely fit within said inner wall of said first column to form a pressure seal therewith.

11. (withdrawn) The high pressure applicator of claim 9, further comprising at least one sealing element mounted to said first end portion and adapted to form a pressure seal between said inner wall and said plunger element.

12. (withdrawn) The high pressure applicator of claim 9, further comprising a handle integrally formed with or affixed to and extending radially from said second column to provide the user a mechanical advantage upon grasping said handle.

13. (withdrawn) The high pressure applicator of claim 11, wherein said at least one sealing element comprises and O-ring.

Application No. 10/039,892  
Page 4 of 12

14. (withdrawn) The high pressure applicator of claim 11, further comprising at least one frictional element mounted to said second end portion and adapted to form a friction fit with said second column at or near said second closed end.

15. (currently amended) The high pressure applicator of claim 3, further comprising threading ~~on for~~ at least a portion of said inner wall of said first column, and wherein said wall of said second column is an external wall comprising threading along at least a portion thereof, said threading of said external wall being engageable with said threading on at least a portion of said inner wall.

16. (Original) The high pressure applicator of claim 15, wherein said threading on said external wall engages with said threading on said inner wall to form a pressure seal therebetween.

17. (previously amended) The high pressure applicator of claim 15, further comprising at least one sealing element mounted to an end portion of said second column and adapted to form or enhance a pressure seal with said inner wall.

18. (Original) The high pressure applicator of claim 17, wherein said at least one sealing element comprises an O-ring.

19. (Original) The high pressure applicator of claim 17, wherein said at least one sealing element comprises a Teflon wrap.

20. (currently amended) The high pressure applicator of claim 1, wherein said handle is integrally formed with or affixed to said first column.

21. (currently amended) The high pressure applicator of claim 15, wherein said ~~threading threads~~ cover only a portion of said second column external wall, an end portion of said second column being relatively smooth.

22. (Original) The high pressure applicator of claim 21, wherein only a portion of said inner wall comprises threads, the remainder of said inner wall being substantially smooth.

Application No. 10/039,892  
Page 5 of 12

23. (Original) The high pressure applicator of claim 22, wherein said relatively smooth end portion comprises a reduced diameter section having an outside diameter less than an inside diameter of said threads on said inner wall, and an enlarged section which closely fits with said substantially smooth inner wall to form a pressure seal therewith.

24. (previously amended) The high pressure applicator of claim 1, wherein said first column comprises a hinged or removable section adapted to swing open or be removed from said first column for drivably engaging said first and second columns.

25. (Original) The high pressure applicator of claim 22, wherein said end portion of said external wall closely fits with said remainder of said inner wall to form a pressure seal therewith.

26. (Original) The high pressure applicator of claim 25, further comprising at least one sealing element mounted to said end portion of said second column and adapted to enhance said pressure seal.

27. (Original) The high pressure applicator of claim 25, wherein said at least one sealing element comprises an O-ring.

28. (withdrawn) The high pressure applicator of claim 1, further comprising a syringe including a barrel portion and a plunger portion, wherein said second column is substantially hollow and comprises an inside wall, an open first end and a closed second end, and wherein said barrel portion is received within said first column and said plunger portion is received within said second column.

29. (withdrawn) The high pressure applicator of claim 28, further comprising threading on said outer wall of said first column and threading on said inner wall of said second column, said threading on said second column being engageable with said threading on said first column.

30. (withdrawn) The high pressure applicator of claim 28, further comprising a handle integrally formed with or affixed to and extending radially from said second column to provide the user a mechanical advantage upon grasping said handle.

Application No. 10/039,892  
Page 6 of 12

31. (withdrawn) The high pressure applicator of claim 28, wherein an end of said barrel portion abuts against said substantially closed end of said first column and an end of said plunger portion abuts against said closed end of said second column, wherein driving of said second column with respect to said first column provides a driving force for advancing said plunger portion within said barrel portion.

32. (withdrawn) The high pressure applicator of claim 29, wherein said barrel portion further comprises a wing or flanged portion adjacent an open end thereof; and

said first column comprises a first portion adjacent said open end and a second portion adjacent said substantially closed end and a transitional portion joining said first and second portions, wherein said first portion has an inside diameter larger than an inside diameter of said second portion, and wherein said transitional portion is adapted to abut against said wing or flanged portion.

33. (withdrawn) The high pressure applicator of claim 1, further comprising a syringe including a barrel portion and a plunger portion, wherein said syringe is received within said first column.

34. (withdrawn) The high pressure applicator of claim 33, further comprising a handle integrally formed with or affixed to and extending radially from said second column to provide the user a mechanical advantage upon grasping said handle.

35. (withdrawn) The high pressure applicator of claim 33, further comprising threading on at least a portion of said inner wall of said first column, and wherein said second column comprises an end adapted to abut an end of said plunger portion and an external wall including threading along at least a portion thereof, said threading of said external wall being engageable with said threading on at least a portion of said inner wall.

36. (withdrawn) The high pressure applicator of claim 35, wherein an end of said barrel portion abuts against said substantially closed end of said first column, wherein driving of said second column with respect to said first column provides a driving force for advancing said plunger portion within said barrel portion.

Application No. 10/039,892  
Page 7 of 12

37. (withdrawn) The high pressure applicator of claim 35, wherein said barrel portion further comprises a wing or flanged portion adjacent an open end thereof; and

said first column comprises a first portion adjacent said open end and a second portion adjacent said substantially closed end and a transitional portion joining said first and second portions, wherein said first portion has an inside diameter larger than an inside diameter of said second portion, and wherein said transitional portion is adapted to abut against said wing or flanged portion.

38. (Cancelled) ~~The high pressure applicator of claim 1, wherein said applicator is capable of generating pressures of at least about 1000 psi.~~

39. (previously amended) The high pressure applicator of claim 1, wherein said applicator is capable of generating pressures of at least 1500 psi.

40. (previously amended) The high pressure applicator of claim 1, wherein said applicator is capable of generating pressures of at least 2000 psi.

41. (previously amended) The high pressure applicator of claim 1, wherein said applicator is capable of generating pressures of at least 2500 psi.

42. (previously amended) The high pressure applicator of claim 1, wherein said applicator is capable of generating pressures of at least 3000 psi.

43. (Original) A high pressure applicator for driving the delivery of a flowable tissue implant material, comprising:

a first column having an inner wall, an outer wall, a first open end and a second substantially closed end having an orifice therethrough;

a second column adapted to overfit at least a portion of said first column, said second column having an inner wall, an outer wall, an open end and a closed end; and

a plunger element having a first end portion adapted to be inserted within said first column and a second end portion adapted to abut said closed end of said second column.

Application No. 10/039,892  
Page 8 of 12

44. (Original) The high pressure applicator of claim 43, further comprising threads on at least a portion of said outer wall of said first column and threads on at least a portion of said inner wall of said second column, said threads on said second column being engageable with said threads on said first column.

45. (Original) The high pressure applicator of claim 43, wherein said first end portion is adapted and configured to closely fit within said inner wall of said first column to form a pressure seal therewith.

46. (Original) The high pressure applicator of claim 43, further comprising at least one sealing element mounted to said first end portion and adapted to form a pressure seal between said inner wall of said first column and said plunger element.

47. (Original) The high pressure applicator of claim 46, wherein said at least one sealing element comprises an O-ring.

48. (Original) The high pressure applicator of claim 43, further comprising at least one frictional element mounted to said second end portion and adapted to form a friction fit with said second column at or near said closed end.

49. (Original) The high pressure applicator of claim 48, wherein said at least one frictional element comprises an O-ring.

50. (Original) The high pressure applicator of claim 43, wherein said second end portion of said plunger element comprises a spherical surface.

51. (Original) The high pressure applicator of claim 43, further comprising a handle fixedly attached to said first column and radially extending therefrom to provide a user a mechanical advantage upon grasping said handle.

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**